

MODEL C03RP-1800

Calender adapt for continuous fabrics:

- Transfer printing
- Direct inks reactivation
- Sublimation printing (with options)
- Thermosetting – “crush” effect

1. CHARACTERISTICS OF HEATING CYLINDER:

- 1.1. Diameter : 350 mm (13,78”).
- 1.2. Width : 1.800 mm (70,87”).
- 1.3. Working width: 1.630 mm (64,17”).

2. HEATING SYSTEM AND TEMPERATURE CONTROL:

- 2.1. The cylinder is heated by one resistor (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.A. system.
- 2.2. The temperature of the cylinder is set by touch screen and regulated by an electronic thermostat and equipped with temperature alarm system and a limitation system of maximum temperature (230 °C).

3. TENSION CONTROLS:

3.1. Tension control for printing material:

- Entry: axial unwinding with disk brake with pneumatic adjustment and fabric manual brake.
- Exit: double roll tangential winding, with possibility of soft or hard winding by transmission management, control by potentiometer.

3.2. Tension control for printing paper:

- Entry: axial unwinding with disk brake with pneumatic adjustment.
- Exit: axial winding with independent motor, adjustable by touch-screen.

3.3. Tension control for protection paper:

- Entry: axial unwinding with disk brake with pneumatic adjustment.
- Exit: axial winding with independent motor, adjustable by touch-screen.

4. OTHER DEVICES INTO MACHINE:

- 4.1. Independent motors with an electronic synchronization system
- 4.2. NOMEX felt with pneumatic tension adjustment system and felt-centring device by means of motorized electric linear actuator.
- 4.3. Incorporated system of felt protection in case of black out and/or compressed air lack
- 4.4. Meter-counter, with alarm to predetermine the length of production runs
- 4.5. General management of the machine, including temperature control by adjustable PLC for the memorization of production data
- 4.6. Front touch-screen keyboard for production data access and programming

5. ROLLS DIAMETER MACHINE WITHOUT OPTIONS:

- Fabric roll diameter in entry 250 mm (9,84”).
- Fabric roll diameter in exit 250 mm (9,84”).
- Printing paper roll diameter in entry 250 mm (9,84”)- Larger diameters on request.
- Printing paper roll diameter in exit 250 mm (9,84”)- Larger diameters on request.
- Protection paper roll diameter in entry 300 mm (11,81”).
- Protection paper roll diameter in exit 300 mm (11,81”).

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

MODEL C03RP-1800

6. TECHNICAL DATA:
 - 6.1. Installed power: 21,34 kW
 - 6.2. Average electrical consumption: 15 kWh
 - 6.3. Compressed air pressure: 4-8 bar
 - 6.4. Mechanic speed: 0.5 ÷ 7 m/min
 - 6.5. Overall dimensions: width 3.210 mm (126,38"). length 1.520 mm (59,84"). height 1.532 mm (60.31").
 - 6.6. Net weight: 2.200 kg
 - 6.7. Machine produced according to CE rules
 - 6.8. Customs tariff: 84 51 80 30

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options