

MODEL S05

Continuous belt press for knitted fabric ironing/finishing, with steaming upper plate

1. MACHINE CHARACTERISTICS

1.1. Planes number: 3 in sequence

- Steaming frontal plane sucking/steaming
- Intermediate lower plane sucking/steaming
- Continuous cooling rear plane in exit
- Built in automatic stacker

1.2. The upper steaming plane, electrically heated, and with adjustable pressure with possibility to utilize the "block" function.

1.3. Plane dimensions: 2.000 mm (78,74") x 1.000 mm (39,37").

2. HEATING AND TEMPERATURE CONTROL

2.1. The upper plate is heated by means of steam and electric resistors controlled by a touch-screen computer.

2.2. Every steaming plane is equipped with a self-heated steam chamber (lower plane) or electrically heated (upper plate) which guarantees dry steam

3. OTHER DEVICES INTO MACHINE

3.1. Automatic, semi-automatic or manual functioning

3.2. Conveyor-belt in polyester

3.3. Built-in automatic stacker

3.4. Alarm for maximum stacker achievement

3.5. Touch-screen computer for 30 regulations and memory for 100 different programs

3.6. Built-in powerful suction fan

3.7. Only supplied without boiler but with steam inlet connections for external boiler

4. TECHNICAL DATA

4.1. Installed power: 7 kW

4.2. Average electric consumption: 4.5 kW/h

4.3. Compressed air pressure: 6-8 bar

4.4. Maximum and optimal steam feeding pressure: 3.5 bar

4.5. Overall dimensions: width 2.550 mm (100,39"). length 4.435 mm (174,6"). height 1.850 mm (72,83").

4.6. Net weight: 2.100 kg

4.7. Machine produced according to CE rules

4.8. Customs tariff: 84 51 30 00

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options