

MODEL C05-3000

Calender adapt for continuous fabrics:

- Transfer printing
- Direct inks reactivation
- Thermosetting – heatsetting
- Heatsetting of “crush” effect

1. CHARACTERISTICS OF HEATING CYLINDER:

- 1.1. Diameter : 500 mm (19,70”)
- 1.2. Width : 3.000 mm (118,11”).
- 1.3. Working Width: 2.800 mm (110,24”).

2. HEATING SYSTEM AND TEMPERATURE CONTROL:

- 2.1. The cylinder is heated by one resistor (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.A. system.
- 2.2. The temperature of the cylinder is set by the touch screen and regulated by an electronic card. The temperature controls equipped with temperature alarm system and a limitation system of maximum temperature (230 °C).

3. TENSION CONTROLS

3.1. Tension control for printing material:

- Entry: axial unwinding with disk brake with pneumatic adjustment and fabric manual brake.
- Exit: double roll tangential winding, with possibility of soft or hard winding by transmission management, control by potentiometer.

3.2. Tension control for printing paper:

- Entry: axial unwinding with disk brake with pneumatic adjustment.
- Exit: axial winding with independent motor, adjustable by touch-screen.

3.3. Tension control for protection paper:

- Entry: axial unwinding with disk brake with pneumatic adjustment.
- Exit: axial winding with independent motor, adjustable by touch-screen.

4. OTHER DEVICES INTO MACHINE

- 4.1. Independent motors with an electronic synchronization system.
- 4.2. NOMEX felt with pneumatic tension adjustment system and felt-centring device by means of motorized electric linear actuator.
- 4.3. Incorporated system for felt protection in case of black out and/or compressed air lack.
- 4.4. Multifunctional electronic meter-counter, with alarm to predetermine the length of production runs.
- 4.5. Temperature cooling system for printed fabric exit, complete with fan.
- 4.6. General management of the machine, including temperature control by adjustable PLC for the memorization of production data.
- 4.7. Front touch-screen keyboard for production data access and programming.
- 4.8. Pneumatic movable paper separator.

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

MODEL C05-3000

5. ROLLS DIAMETER MACHINE WITHOUT OPTIONS:

- Fabric roll diameter in entry 400 mm (15,75").
- Fabric roll diameter in exit 400 mm (15,75").
- Printing paper roll diameter in entry 300 mm (11,81") - Larger diameters on request.
- Printing paper roll diameter in exit 300 mm (11,81") - Larger diameters on request.
- Protection paper roll diameter in entry 400 mm (15,75").
- Protection paper roll diameter in exit 400 mm (15,75").

6. TECHNICAL DATA

6.1. Installed power: 39,8 kW

6.2. Average electric consumption: 27,6 kWh

6.3. Compressed air pressure: 6-8 bar

6.4. Mechanic speed: 0.5 ÷ 7.5 m/min

6.5. Overall dimensions (with platform): width 4.550 mm (179,13"). length 2.330 mm (91,73"). height 2.195 mm (86,41").

6.6. Net weight: 5.350 kg

6.7. Machine produced according to EC rules

6.8. Customs tariff: 84 51 80 30

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options