

MODEL T02-2000

Special calender for pieces or continuous fabrics, used for:

- Transfer printing
- Direct inks reactivation
- Thermosetting - heatsetting

Versatile and polyvalent calender, developed for transfer printing of all the follows work conditions, according to required options:

- Printing paper in roll and material to be printed in roll
- Printing paper in roll and material to be printed in pieces
- Printing paper in sheets and material to be printed in pieces

1. CHARACTERISTICS OF HEATING CYLINDER:

- 1.1. Diameter : 200 mm (7,87").
- 1.2. Width : 2.000 mm (78,74").
- 1.3. Working Width: 1.850 (72,83").

2. HEATING SYSTEM AND TEMPERATURE CONTROL:

- 2.1. The cylinder is heated by one resistor (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.a system.
- 2.2. The temperature of the cylinder is set by a touch screen and is regulated by an electronic card. The temperature control is equipped with temperature alarm system and a limitation system of maximum temperature (230 °C).

3. TENSION CONTROLS:

3.1. Tension control for printing material in roll:

Entry: axial unwinding with manual brake

Exit: axial motorised winding with pneumatic device for motion transmission from the main motor

3.2. Tension control for printing paper in roll:

Entry: axial unwinding with disk brake with pneumatic adjustment

Exit: axial motorised winding with pneumatic device for motion transmission from the main motor

3.3. Tension control for protection paper:

Entry: axial unwinding with disk brake with pneumatic adjustment

Exit: axial motorised winding with pneumatic device for motion transmission from the main motor

4. OTHER DEVICES INTO MACHINE:

- 4.1. Short front working table, 800 mm
- 4.2. Single motor
- 4.3. NOMEX felt with pneumatic tension adjustment system and automatic felt-centering device
- 4.4. Incorporated system of felt protection in case of black out and/or compressed air lack
- 4.5. Meter-counter, with alarm to predetermine the length of production runs
- 4.6. General management of the machine, including temperature control by adjustable PLC for the memorization of production data
- 4.7. Front touch-screen keyboard for production data access and programming

5. ROLLS DIAMETER MACHINE WITHOUT OPTIONS:

- Fabric roll diameter in entry 250 mm (9,84").
- Fabric roll diameter in exit 250 mm (9,84").

All data and technical features are purely indicative and subjected to changes without prior notice

MODEL T02-2000

- Printing paper roll diameter in entry 250 mm (9,84") - Larger diameters on request.
- Printing paper roll diameter in exit 250 mm (9,84") - Larger diameters on request.
- Protection paper roll diameter in entry 250 mm (9,84").
- Protection paper roll diameter in exit 250 mm (9,84").

6. TECHNICAL DATA:

6.1. Installed power: 14 kW

6.2. Average electric consumption: 9,3 kW/h

6.3. Compressed air pressure: 3 - 8 bar

6.4. Mechanic speed: 0.1 - 1.7 m/min

6.5. Overall dimensions (with front table): width 3.290 mm (129,53"). length 2.000 mm (78.74"). height 1.440 mm (56,70").

6.6. Net weight: 1.300 kg

6.7. Machine produced according to CE rules

6.8. Customs tariff: 84 51 80 30

All data and technical features are purely indicative and subjected to changes without prior notice

INNOVATION
SPEED
FLEXIBILITY
PROJECT&DESIGN
INSTALLATION AND ASSISTANCE



Monti Antonio S.p.A.
Head Office: via dell'Electronica n°5, 36016 Thiene (VI) Italy
Operation and Administration: via della Fisica n°6, 36016 Thiene (VI) Italy
T. +39 0445 364619 +39 0445 364707 - sales@montiantonio.com
www.montiantonio.com