

MODEL N10P-750

Polyvalent calender for ribbons and continuous narrow fabric, used for:

- Transfer printing
- Direct inks reactivation
- Thermosetting – heatsetting
- Film/web thermobonding
- Plastification and coating with film
- Transfer printing of polyurethane, PVC and synthetic leather
- Metallization and gold lamination
- Transfer of special effects (es.: snake skin)
- Embossing using release paper

1. CHARACTERISTICS OF PRINTING CYLINDER:

- 1.1. Diameter: 1.000 mm (39,37”).
- 1.2. Width: 750 mm (29,53”).
- 1.3. Working width: 650 mm (25,59”).

2. HEATING SYSTEM AND TEMPERATURE CONTROL:

- 2.1. The cylinder is heated by resistors (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.A. system.
- 2.2. The temperature of the cylinder is set by a touch screen and is regulated through an electronic card. The temperature control is equipped with temperature alarm system and a limitation system of maximum temperature (230 °C).

3. TENSION CONTROLS:

- 3.1. Tension control for material:
 - Entry: little rolls with separators discs in PVC.
 - Exit: n°6 rolls to place ribbons into appropriate boxes, single independent motorization.
- 3.2. Tension control for printing paper:
 - Entry: little rolls with separators discs in PVC (option: axial unwinder for digital printing paper).
 - Exit: special motorized roll with frictioned independent rings, pneumatically controlled.
- 3.3. Tension control for protection paper:
 - Entry: axial unwinding with disk brake, pneumatically adjusted.
 - Exit: axial winder with independent motor and adjusted by potentiometer.

4. OTHER DEVICES INTO MACHINE:

- 4.1. Independent motors with an electronic synchronization system.
- 4.2. NOMEX felt with pneumatique tension adjustment system and automatic felt-centering device.
- 4.3. Meter-counter, with alarm to predetermine the length of production runs.
- 4.4. Slamer roll in entry for ribbons coming from boxes.
- 4.5. Incorporated system of felt protection in case of black out and/or lack of compressed air.
- 4.6. General management of the machine, including temperature control by adjustable PLC for the memorization of production data.
- 4.7. Front touch-screen keyboard in front of the machine for production various accesses and programming.
- 4.8. Pressing roll Ø 165 mm covered by silicon rubber for high temperatures, controlled by touch-screen, able to apply a pressure up to 9 Kg for linear centimetre at 6 bar.
- 4.9. Control of the pressing roll by manometer and pressure regulator to stop single-beam photocells only when the roll is in opening position.

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

MODEL N10P-750

4.10. Safety system for the pressing roll by single-beam photocells both on the front and the rear side of the machine.

5. ROLLS DIAMETER MACHINE WITHOUT OPTIONS:

- Fabric roll diameter in entry 250 mm (9,84").
- Direct discharge.
- Printing paper roll diameter in entry 250 mm (9,84").
- Printing paper roll diameter in exit 250 mm (9,84").
- Protection paper roll diameter in entry 400 mm (15,75").
- Protection paper roll diameter in exit 400 mm (15,75").

6. TECHNICAL DATA:

- 6.1. Installed power: 38,52 kW.
- 6.2. Average electrical consumption: 25,90 kW/h.
- 6.3. Power in ECONOMY mode: 26,52 kW.
- 6.4. Compressed air pressure: 6-8 bar.
- 6.5. Mechanic speed: 1 ÷ 20 m/min.
- 6.6. Overall dimensions: width 2.190 mm (86,22"), length 4.990 mm (196,46"), height 2.630 mm (103,54").
- 6.7. Net weight: 2.750 kg.
- 6.8. Machine produced according to CE rules.
- 6.9. Customs tariff: 84 51 80 80.

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options