

## MODEL P20VSP-4050X1600

Double flat bed press used for:

- Transfer printing with **vacuum** system for deeper inks penetration.
- Transfer printing
- Thermosetting - heatsetting
- Film/web thermobonding
- Plastification and coating with film
- Metallization and gold lamination
- Transfer of special effects (es.: snake skin)

### 1. CHARACTERISTICS OF PRINTING PLANES:

- 1.1. Planes number : 2
- 1.2. Dimensions: 4.050 mm (159,5") x 1.600 mm (63").
- 1.3. Working dimensions with VSP: 3.960 mm (156") x 1.510 mm (59,5")

### 2. HEATING AND TEMPERATURE CONTROL:

- 2.1. The printing plane is heated by electrical resistors.
- 2.2. The temperature of the printing plane is adjustable up to 230°C and controlled by touch-screen by n° 3 independent temperature controls.

### 3. OTHER DEVICES INTO MACHINE:

- 3.1. Manual, semi-automatic or automatic functions
- 3.2. Motorized movement of the heated plate
- 3.3. Automatic and recordable stroke times
- 3.4. Hydraulic pressure
- 3.5. Weekly programmer for automatic switching on and off
- 3.6. Equipped with vacuum pump
- 3.7. Normal printing (no vacuum): + sheets + felts (optional)

### 4. TECHNICAL DATA:

- 4.1. Installed power: 56,5 kW
- 4.2. Average electric consumption: 37 kW/h
- 4.3. Compressed air pressure: 4 bar
- 4.4. Average air pressure consumption: 0,2 Lt/min
- 4.5. Overall dimensions (without vacuum pump): width 2.200 mm (87"). length 8.400 mm (330,70"). height 1.980 mm (78").
- 4.6. Net weight: 13.000 kg
- 4.7. Machine produced according to CE rules
- 4.8. Customs tariff: 84 51 80 30

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options