

## MODEL N05-750

Polyvalent calender for ribbons and continuous narrow fabric, used for:

- Transfer printing
- Direct inks reactivation
- Thermosetting – heatsetting

### 1. CHARACTERISTICS OF PRINTING CYLINDER:

- 1.1. Diameter: 500 mm (19,69”).
- 1.2. Width: 750 mm (29,53”).
- 1.3. Working width: 650 mm (25,59”).

### 2. HEATING SYSTEM AND TEMPERATURE CONTROL:

- 2.1. The cylinder is heated by a resistor (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.A. system.
- 2.2. The temperature of the cylinder is set by a touch screen and is regulated through an electronic card. The temperature control is equipped with temperature alarm system and a limitation system of maximum temperature (230 °C).

### 3. TENSION CONTROLS:

- 3.1. Tension control for material:
  - Entry: little rolls with separators discs in PVC.
  - Exit: n°6 rolls to place ribbons into appropriate boxes, single independent motorization.
- 3.2. Tension control for printing paper:
  - Entry: little rolls with separators discs in PVC (option: axial unwinder for digital printing paper).
  - Exit: special motorized roll with frictioned independent rings, pneumatically controlled.
- 3.3. Tension control for protection paper:
  - Entry: axial unwinding with disk brake, pneumatically adjusted.
  - Exit: axial winder with independent motor and adjusted by potentiometer.

### 4. OTHER DEVICES INTO MACHINE:

- 4.1. Independent motors with an electronic synchronization system.
- 4.2. NOMEX felt with pneumatique tension adjustment system and automatic felt-centering device.
- 4.3. Meter-counter, with alarm to predetermine the length of production runs.
- 4.4. Slamer roll in entry for ribbons coming from boxes.
- 4.5. Incorporated system of felt protection in case of black out and/or lack of compressed air.
- 4.6. General management of the machine, including temperature control by adjustable PLC for the memorization of production data.
- 4.7. Front touch-screen keyboard in front of the machine for production various accesses and programming.

### 5. ROLLS DIAMETER MACHINE WITHOUT OPTIONS:

- Fabric roll diameter in entry 250 mm (9,84”).
- Direct discharge.
- Printing paper roll diameter in entry 250 mm (9,84”).
- Printing paper roll diameter in exit 250 mm (9,84”).
- Protection paper roll diameter in entry 250 mm (9,84”).
- Protection paper roll diameter in exit 250 mm (9,84”).

### 6. TECHNICAL DATA:

- 6.1. Installed power: 14 kW.

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

## MODEL N05-750

- 6.2. Average electrical consumption: 9,8 kW/h.
- 6.3. Compressed air pressure: 6-8 bar.
- 6.4. Mechanic speed: 1 ÷ 15 m/min.
- 6.5. Overall dimensions: width 2.160 mm (85,04"), length 4.310 mm (169,70"), height 2.510 mm (98,82").
- 6.6. Net weight: 1.250 kg.
- 6.7. Machine produced according to CE rules.
- 6.8. Customs tariff: 84 51 80 30.

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

INNOVATION  
SPEED  
FLEXIBILITY  
PROJECT&DESIGN  
INSTALLATION AND ASSISTANCE



Monti Antonio S.p.A.  
Head Office: via dell'Electronica n°5, 36016 Thiene (VI) Italy  
Operation and Administration: via della Fisica n°6, 36016 Thiene (VI) Italy  
T. +39 0445 364619 +39 0445 364707 - sales@montiantonio.com  
[www.montiantonio.com](http://www.montiantonio.com)