Machine for:

- impregnation
- Inks reactivation

1. HEATING CYLINDER'S CHARACTERISTICS:

- 1.1. Diameter: 800 mm (31,50").
- 1.2. Width: 2.000 mm (78,74").
- 1.3. Working width: 1.800 mm (70,87").
- 2. HEATING SYSTEM AND TEMPERATURE CONTROL:
 - 2.1. The cylinder is heated by one resistor (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.A system.
 - 2.2. The temperature of the cylinder is regulated by a touch screen and is regulated by an electronic card. The temperature control is equipped with temperature alarm system and a limitation system of maximum temperature (230 °C).
- 3. TENSION CONTROLS:
 - 3.1. Tension control for material to be treated:
 - Entry: axial unwinding with disk brake with pneumatic adjustment and fabric manual brake
 - Exit: independent double-roller tangential winding, possibility of «soft» or «hard» winding by transmission management, potentiometer control
- 4. OTHER DEVICES INTO MACHINE:
 - 4.1. Independent motors with an electronic synchronization system
 - 4.2. Meter-counter, with alarm to predetermine the length of production runs
 - 4.3. General management of the machine, including temperature control by adjustable PLC for the memorization of production data
 - 4.4. Removable and interchangeable AISI 304 tank for impregnation liquid
 - 4.5. Recirculation system of the impregnating liquid
 - 4.6. Squeezer with rubberized rollers, one of which is stationary motorized and one is idle and controlled by pneumatic pistons
 - 4.7. Fumes hood with condensate separation
 - 4.8. Front touch-screen keyboard for production data access and programming

5. ROLLS DIAMETER MACHINE WITHOUT OPTIONS:

- Fabric roll diameter in entry 400 mm (15,75").
- Fabric roll diameter in exit 400 mm (15,75").

6. TECHNICAL DATA:

- 6.1. Installed power: to be confirmed.
- 6.2. Average electric consumption: to be confirmed.
- 6.3. Power in ECONOMY MODE: to be confirmed.
- 6.4. Compressed air pressure: to be confirmed.
- 6.5. Mechanic speed: to be confirmed.
- 6.6. Overall dimensions: to be confirmed.
- 6.7. Net weight: to be confirmed.
- 6.8. Machine produced according to CE rules
- 6.9. Customs tariff: 84 51 80 80

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options





onti Antonio S.p.A. and Officer via dell'Elettronica nº1, 36019 Thieve (VI) Raly pention and Adata Statella - F.-38018 Thieve (VI) Raly 430 det8 344819 - F.-38 0445 34403 430 det Satella - F.-38 0445 34403