

MODEL S04

Sucking and steaming double press for knitwear ironing/finishing, with upper steaming plate

1. MACHINE CHARACTERISTICS

- 1.1. Planes number: 2 sucking and steaming
- 1.2. Oscillating/parallel upper plane, steaming, electrically heated and with adjustable pressure with possibility to utilize the "block" function.
- 1.3. Plane dimensions: 1.800 mm (70,87") x 920 mm (36,22").

2. HEATING AND TEMPERATURE CONTROL

- 2.1. The oscillating/parallel upper plate is heated by means electric resistors controlled by electronic thermostat
- 2.2. Every steaming plane is equipped with a self-heated steam chamber (lower plane) or electrically heated (upper plate) which guarantees dry steam

3. OTHER DEVICES INTO MACHINE

- 3.1. Automatic, semi-automatic or manual functioning
- 3.2. Microprocessor which memorizes all different working process
- 3.3. Built-in powerful suction fan
- 3.4. Only supplied without boiler but with steam inlet connections for external boiler

4. TECHNICAL DATA

- 4.1. Installed power: 6 kW
- 4.2. Average electric consumption: 4 kW/h
- 4.3. Compressed air pressure: 6-8 bar
- 4.4. Maximum and optimal steam feeding pressure: 3.5 bar
- 4.5. Overall dimensions: width 3.950 mm (155,51"). length 1.600 mm (62,99"). height 2.300 mm (90,55").
- 4.6. Net weight: 1.250 kg
- 4.7. Machine produced according to CE rules
- 4.8. Customs tariff: 84 51 30 00

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options